



Note:  
 Pin 1:Right  
 Pin 2:Top  
 Pin 3:Left  
 Pin 4:Bottom  
 Pin Pitch:2.54mm  
 Total Thickness:1.4± 0.1 mm  
 Surface Hardness:3H  
 Optical Clarity:80%  
 Operating Temperature:0°C ~ 50°C  
 Operating Voltage:DC3 ~ 12V  
 Resistance:200ohm ~ 900ohm  
 Linearity:< 1.5%  
 Faceplate Surface:anti-glare coating  
 Operation Pressure:35g~60g  
 Storage Temperature:-20°C ~ 70°C  
 Message Noise: 5 m sec~15 m sec  
 Operating Current:5mA ~ 25mA  
 Isolation Resistance:DC25V 20Mohm UP  
 Endurance Test: Over 1 million strikes  
 V.A. : VIEW AREA  
 A.A. : ACTIVE AREA

瞄準科技有限公司 AIM TOUCH TECHNOLOGY CO.,LTD. 	DATE : 2000/09/07	Part Number	ITO Film Type	Glass Type	Glass Thickness	Finished Part Thickness
	MODEL :	AIM-4R-0540-M01-G0N	ANTI GLARE	General	0.7mm	1.0mm±0.1
	AIM-4R-0540-M01	AIM-4R-0540-M01-G07SN	ANTI GLARE	chemical strengthen	0.7mm	1.0mm±0.1
		AIM-4R-0540-M01-G1N	ANTI GLARE	General	1.1mm	1.4mm±0.1

NOTE : All indications are the millimeters.